

I CLAIM:

1. A spinal implant for insertion between adjacent vertebral bodies, comprising:
opposed upper and lower surfaces adapted to contact each of the adjacent vertebral
bodies, respectively from within the disc space;
5 a leading end for insertion between the adjacent vertebral bodies;
a trailing end opposite said leading end, said trailing end having an exterior surface and
an outer perimeter with an upper edge and a lower edge adapted to be oriented toward the
adjacent vertebral bodies, respectively; and
a plurality of bone screw receiving holes in said trailing end, at least one of which is
10 adapted to only partially circumferentially surround a trailing end of a bone screw adapted to
be received therein, at least one of said bone screw receiving holes passing through said
exterior surface and one of said edges so as to permit the trailing end of the bone screw to
protrude beyond said one of said edges.
- 15 2. The implant of claim 1, wherein said implant is a fusion implant.
3. The implant of claim 1, wherein a plane of said trailing end is curved.
4. The implant of claim 1, wherein said implant has a height equal to the distance between
20 the adjacent vertebral bodies where installed into the disc space when installed.
5. The implant of claim 1, wherein said outer perimeter of said trailing end has at least one
gap therein for permitting a portion of at least an outer diameter of a bone screw to protrude

beyond said outer perimeter of said trailing end, said gap in said bone screw receiving hole dimensioned to be less than the outer diameter of the bone screw.

6. The implant of claim 1, wherein at least one of said bone screw receiving holes passing
5 through said exterior surface and one of said edges is C-shaped in cross section.

7. The implant of claim 1, wherein at least one of said bone screw receiving holes passing through said exterior surface and one of said edges has a partial circumference intersecting with the outer perimeter of said trailing end.

8. The implant of claim 1, wherein said trailing end is relieved to allow for a head of a bone screw inserted into one of said bone screw receiving holes to be at least partially recessed.

9. The implant of claim 1, wherein at least two of said plurality of bone screw receiving
15 holes are at different distances from the mid-longitudinal axis of said implant.

10. The implant of claim 1, wherein said trailing end is generally quadrilateral in shape.

11. The implant of claim 1, wherein at least one pair of said plurality of bone screw receiving
20 holes are adapted to orient bone screws to be received therein at an angle to a horizontal mid-longitudinal plane of said implant passing through said leading and trailing ends.

12. The implant of claim 11, wherein said plurality of bone screw receiving holes includes a pair of screw receiving holes along said upper edge and a pair of screw receiving holes along said lower edge, one of said pair of bone screw receiving holes being adapted to position bone screws in a convergent relationship to one another.

5

13. The implant of claim 12, wherein the other of said pair of bone screw receiving holes is adapted to position bone screws in a divergent relationship to one another.

10

14. The implant of claim 11, wherein said angle is greater than 15 degrees and less than 60 degrees.

15. The implant of claim 1, further comprising at least one lock for retaining a bone screw within said implant.

15

16. The implant of claim 15, wherein said at least one lock retains a plurality of bone screws to said implant.

20

17. The implant of claim 1, further comprising at least one bone screw having a leading end for placement in the vertebral body and a trailing end opposite said leading end adapted to cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within one of said plurality of bone screw receiving holes of said implant.

18. The implant of claim 1, wherein said implant comprises one of bone and bone growth promoting material.

19. The implant of claim 18, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

20. The implant of claim 1, wherein said implant is treated with a bone growth promoting substance.

21. The implant of claim 1, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

22. The implant of claim 1, wherein said implant is formed of a porous material.

23. The implant of claim 1, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

24. The implant of claim 23, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

25. The implant of claim 1, in combination with a chemical substance to inhibit scar formation.
26. A spinal implant for insertion between adjacent vertebral bodies, comprising:
5 opposed upper and lower surfaces adapted to contact one each of the adjacent vertebral bodies from within the disc space;
 a leading end for insertion between the adjacent vertebral bodies; and
 a trailing end opposite said leading end, said trailing end having an upper edge and a lower edge, said trailing end being adapted to only partially circumferentially surround the
10 circumference of at least one bone screw adapted to be received therein.
27. The implant of claim 26, wherein said implant is a fusion implant.
28. The implant of claim 26, wherein said trailing end is curved.
- 15 29. The implant of claim 26, wherein said implant has a height equal to the distance between the adjacent vertebral bodies where installed into the disc space when installed.
- 20 30. The implant of claim 26, wherein at least one of said upper and lower edges of said trailing end has at least one gap therein for permitting a portion of at least an outer diameter of a bone screw to protrude beyond said at least one of said upper and lower edges of said trailing end, said gap being dimensioned to be less than the outer diameter of the bone screw.

31. The implant of claim 26, wherein said trailing end is relieved to allow for a head of a bone screw inserted into said trailing end to be at least partially recessed.
32. The implant of claim 26, wherein said trailing end is adapted to orient bone screws to be received therein at an angle to a horizontal mid-longitudinal plane of said implant passing through said leading and trailing ends.
33. The implant of claim 32, wherein said trailing end has a pair of screw receiving holes along said upper edge and a pair of screw receiving holes along said lower edge, one of said pair of bone screw receiving holes being adapted to position bone screws in a convergent relationship to one another.
34. The implant of claim 33, wherein the other of said pair of bone screw receiving holes is adapted to position bone screws in a divergent relationship to one another.
35. The implant of claim 26, further comprising at least one lock for retaining a bone screw within said implant.
36. The implant of claim 35, wherein said at least one lock retains a plurality of bone screws to said implant.
37. The implant of claim 26, further comprising at least one bone screw having a leading end for placement in the vertebral body and a trailing end opposite said leading end adapted to

cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within said trailing end of said implant.

38. The implant of claim 26, wherein said implant comprises one of bone and bone growth promoting material.

39. The implant of claim 38, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

40. The implant of claim 26, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

41. The implant of claim 26, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

42. The implant of claim 41, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

43. The implant of claim 26, in combination with a chemical substance to inhibit scar formation.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

44. A spinal implant for insertion between adjacent vertebral bodies, comprising:
opposed upper and lower portions adapted to contact each one of the adjacent
vertebral bodies from within the disc space;
a leading end for insertion between the adjacent vertebral bodies; and
a trailing end opposite said leading end, said trailing end having an upper edge, a lower
edge, and a maximum height therebetween, said trailing end being adapted to receive at least
a portion of a bone screw passing therein that extends beyond said maximum height
immediately adjacent thereto.
45. The implant of claim 44, wherein said implant is a fusion implant.
46. The implant of claim 44, wherein said trailing end is curved.
47. The implant of claim 44, wherein said implant has a height equal to the distance
between the adjacent vertebral bodies where installed into the disc space when installed.
48. The implant of claim 1, wherein at least one of said upper and lower edges of said
trailing end has at least one gap therein for permitting a portion of at least an outer diameter of
a bone screw to protrude beyond said at least one of said upper and lower edges of said
trailing end, said gap being dimensioned to be less than the outer diameter of the bone screw.

49. The implant of claim 44, wherein said trailing end is relieved to allow for a head of a bone screw inserted into said trailing end to be at least partially recessed.
50. The implant of claim 44, wherein said trailing end is adapted to orient bone screws to be received therein at an angle to a horizontal mid-longitudinal plane of said implant passing through said leading and trailing ends.
51. The implant of claim 50, wherein said trailing end has a pair of screw receiving holes along said upper edge and a pair of screw receiving holes along said lower edge, one of said pair of bone screw receiving holes being adapted to position bone screws in a convergent relationship to one another.
52. The implant of claim 51, wherein the other of said pair of bone screw receiving holes is adapted to position bone screws in a divergent relationship to one another.
53. The implant of claim 44, further comprising at least one lock for retaining a bone screw within said implant.
54. The implant of claim 53, wherein said at least one lock retains a plurality of bone screws to said implant.
55. The implant of claim 44, further comprising at least one bone screw having a leading end for placement in the vertebral body and a trailing end opposite said leading end adapted to

cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within said trailing end of said implant.

56. The implant of claim 44, wherein said implant comprises one of bone and bone growth promoting material.

57. The implant of claim 56, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

58. The implant of claim 44, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

59. The implant of claim 44, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

60. The implant of claim 59, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

61. The implant of claim 44, in combination with a chemical substance to inhibit scar formation.

62. A spinal implant for insertion between adjacent vertebral bodies, comprising:
opposed upper and lower surfaces adapted to contact each one of the adjacent
vertebral bodies from within the disc space;
5 a leading end for insertion between the adjacent vertebral bodies; and
a trailing end opposite said leading end, said trailing end having a plurality of bone
screw receiving holes, an upper edge, a lower edge, and a maximum height therebetween,
said maximum height of said trailing end being adapted to be less than the sum of the
maximum diameter of two bone screws adapted to be inserted in said bone screw receiving
10 holes, said bone screw receiving holes being adapted to incompletely circumferentially receive
at least one of the bone screws.
63. The implant of claim 62, wherein said implant is a fusion implant.
- 15 64. The implant of claim 62, wherein said trailing end is curved.
65. The implant of claim 62, wherein said implant has a height equal to the distance
between the adjacent vertebral bodies where installed into the disc space when installed.
- 20 66. The implant of claim 62, wherein at least one of said upper and lower edges of said
trailing end has at least one gap therein for permitting a portion of at least an outer diameter of
a bone screw to protrude beyond said at least one of said upper and lower edges of said

trailing end, said gap in said bone screw receiving hole dimensioned to be less than the outer diameter of the bone screw.

67. The implant of claim 62, wherein at least one of said bone screw receiving holes is C-shaped in cross section.

68. The implant of claim 62, wherein said trailing end is relieved to allow for a head of a bone screw inserted into one of said bone screw receiving holes to be at least partially recessed.

69. The implant of claim 62, wherein at least one pair of said plurality of bone screw receiving holes are adapted to orient bone screws to be received therein at an angle to a horizontal mid-longitudinal plane of said implant passing through said leading and trailing ends.

70. The implant of claim 70, wherein said plurality of bone screw receiving holes includes a pair of screw receiving holes along said upper edge and a pair of screw receiving holes along said lower edge, one of said pair of bone screw receiving holes being adapted to position bone screws in a convergent relationship to one another.

71. The implant of claim 70, wherein the other of said pair of bone screw receiving holes is adapted to position bone screws in a divergent relationship to one another.

72. The implant of claim 62, further comprising at least one lock for retaining a bone screw within said implant.
73. The implant of claim 72, wherein said at least one lock retains a plurality of bone screws to said implant.
74. The implant of claim 62, further comprising at least one bone screw having a leading end for placement in the vertebral body and a trailing end opposite said leading end adapted to cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within one of said plurality of bone screw receiving holes of said implant.
75. The implant of claim 62, wherein said implant comprises one of bone and bone growth promoting material.
76. The implant of claim 75, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.
77. The implant of claim 62, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990

78. The implant of claim 62, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

79. The implant of claim 62, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

80. The implant of claim 62, in combination with a chemical substance to inhibit scar formation.

81. A spinal fusion implant for insertion between adjacent vertebral bodies, comprising:
an implant having:
opposed upper and lower surfaces adapted to contact each of the opposed adjacent vertebral bodies from within the disc space;
a leading end for insertion between the adjacent vertebral bodies;
a trailing end opposite said leading end, said trailing end having an exterior surface and an outer perimeter with an upper edge and a lower edge adapted to be oriented toward the adjacent vertebral bodies, respectively; and
a plurality of bone screw receiving holes in said trailing end, at least one of which is adapted to only partially circumferentially surround the trailing end of a bone screw adapted to be received therein, at least one of said screw receiving holes passing through said exterior

surface and one of said edges so as to permit the bone screw to protrude over one of said edges within a plane of said trailing end; and

at least one bone screw, said screw having:

a leading end for placement in the vertebral body; and opposite,

5 a trailing end adapted to cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within said implant.

82. The implant of claim 81, wherein said implant is a fusion implant.

10 83. The implant of claim 81, wherein said plane of said trailing end is curved.

84. The implant of claim 81, wherein said implant has a height equal to the distance between the adjacent vertebral bodies where installed into the disc space when installed.

15 85. The implant of claim 81, wherein said outer perimeter of said trailing end has at least one gap therein for permitting a portion of at least an outer diameter of a bone screw to protrude beyond the outer perimeter of said trailing end, said gap in said bone screw receiving hole dimensioned to be less than the outer diameter of the bone screw.

20 86. The implant of claim 81, wherein at least one of said bone screw receiving holes passing through said exterior surface and one of said edges is C-shaped in cross section.

87. The implant of claim 81, wherein at least one of said bone screw receiving holes passing through said exterior surface and one of said edges has a partial circumference intersecting with the outer perimeter of said trailing end.

5 88. The implant of claim 81, wherein said trailing end is relieved to allow for a head of a bone screw inserted into one of said bone screw receiving holes to be at least partially recessed.

89. The implant of claim 81, wherein at least one pair of said plurality of bone screw receiving holes are adapted to orient bone screws to be received therein at an angle to a horizontal mid-longitudinal plane of said implant passing through said leading and trailing ends.

90. The implant of claim 89, wherein said plurality of bone screw receiving holes includes a pair of screw receiving holes along said upper edge and a pair of screw receiving holes along said lower edge, one of said pair of bone screw receiving holes being adapted to position bone screws in a convergent relationship to one another,

91. The implant of claim 90, wherein the other of said pair of bone screw receiving holes is adapted to position bone screws in a divergent relationship to one another.

92. The implant of claim 81, further comprising at least one lock for retaining a bone screw within said implant.

93. The implant of claim 92, wherein said at least one lock retains a plurality of bone screws to said implant.

94. The implant of claim 81, wherein said implant comprises one of bone and bone growth promoting material.

95. The implant of claim 94, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

96. The implant of claim 81, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

97. The implant of claim 81, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

98. The implant of claim 97, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

99. The implant of claim 81, in combination with a chemical substance to inhibit scar formation.

100. An interbody spinal implant for insertion between adjacent vertebral bodies, comprising:
opposed upper and lower surfaces adapted to contact each of the adjacent vertebral
bodies, respectively from within the disc space;
- 5 a leading end for insertion between the adjacent vertebral bodies; and
a trailing end opposite said leading end, said trailing end having an exterior surface and
an outer perimeter with an upper edge and a lower edge adapted to be oriented toward the
adjacent vertebral bodies, respectively; said outer perimeter having at least one gap therein for
permitting a portion of a bone screw to protrude over the outer perimeter of said trailing end
10 within a plane of said trailing end, said gap being sufficient to retain a trailing end of the bone
screw.
101. The implant of claim 100, wherein said implant is a fusion implant.
102. The implant of claim 100, wherein said trailing end is curved.
103. The implant of claim 100, wherein said implant has a height equal to the distance
between the adjacent vertebral bodies where installed into the disc space when installed.
- 20 104. The implant of claim 100, wherein at least one of said bone screw receiving holes
passing through said exterior surface and one of said edges is C-shaped in cross section.

111. The implant of claim 110, wherein said at least one lock retains a plurality of bone screws to said implant.

112. The implant of claim 100, further comprising at least one bone screw having a leading end for placement in the vertebral body and a trailing end opposite said leading end adapted to cooperatively engage said implant so as to prevent the further advancement of the screw into the bone and to be retained within one of said plurality of bone screw receiving holes of said implant.

113. The implant of claim 100, wherein said implant comprises one of bone and bone growth promoting material.

114. The implant of claim 113, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

115. The implant of claim 100, wherein said implant comprises at least one of the following materials: metal, titanium, plastic, and ceramic.

116. The implant of claim 100, wherein said implant has an interior surface and a hollow defined therein, said hollow being capable of containing bone growth promoting material.

117. The implant of claim 116, wherein said bone growth promoting material is selected from one of bone morphogenetic protein, hydroxyapatite, and genes coding for the production of bone.

5 118. The implant of claim 100, in combination with a chemical substance to inhibit scar formation.